

ALPINE MODEL COMPARISON CHART



V SERIES



PRO SERIES



CALL TOLL FREE: 866-246-5634

www.AlpineShredders.com
Info@AlpineShredders.com

TRUCK SPECS	V19	V26	V33	EVOLUTION	STAK	V-MAX
Chassis Manufacturer:	International	International	International	International	Peterbilt	International
Chassis Model:	TerraStar	4300 DuraStar	4300 DuraStar	4300 DuraStar	337	4400 DuraStar
Standard Engine:	MaxxForce 7	MaxxForce 7	MaxxForce 7	MaxxForce 7	Paccar PX-8	MaxxForce 9
HP - Torque:	300 hp - 660 lb/ft	220 hp - 560 lb/ft	240 hp - 620 lb/ft	220 hp - 560 lb/ft	260 hp - 800 lb/ft	315 hp - 950 lb/ft
Transmission:	Allison Automatic	Allison Automatic	Allison Automatic	Allison Automatic	Allison Automatic	Allison Automatic
Rims:	Steel	Aluminium	Aluminium	Aluminium	Aluminium	Aluminium
Interior:	AM-FM / PW / PDL / Air / Cruise / Tilt	AM-FM / PW / PDL / Air / Cruise / Tilt	AM-FM / PW / PDL / Air / Cruise / Tilt	AM-FM / PW / PDL / Air / Cruise / Tilt	AM-FM / PW / PDL / Air / Cruise / Tilt	AM-FM / PW / PDL / Air / Cruise / Tilt
Fuel - Capacity:	40 USG / ULSD	50 USG / ULSD	50 USG / ULSD	50 USG / ULSD	70 USG / ULSD	120 USG / ULSD
GVWR:	19,500 ⁽¹⁾	26,000 ⁽¹⁾	33,000 ⁽¹⁾	26,000 ⁽¹⁾	33,000 ⁽¹⁾	33,000 ⁽¹⁾
Payload:	5,000 lbs ⁽²⁾	9,000 lbs ⁽²⁾	13,000 lbs ⁽²⁾	8,500 lbs ⁽²⁾	10,000 lbs ⁽²⁾	10,000 lbs ⁽²⁾
Overall Length:	25' 6"	25' 6"	31'	26' 6"	32'	32'
Body Type:	FRP	FRP	FRP	Aerodynamic / FRP	Aerodynamic / FRP	Aerodynamic / FRP
SHREDDER SPECS	V19	V26	V33	EVOLUTION	STAK	V-MAX
Shredder:	Alpine 512	Alpine 512	Alpine 512	Alpine 720	Alpine 720	Alpine 720
Shafts:	6" OD - 5/8" cut	6" OD - 5/8" cut	6" OD - 5/8" cut	8" OD - 5/8" cut	8" OD - 5/8" cut	8" OD - 5/8" cut
Performance:	3,750 lbs/hour ⁽³⁾	4,500 lbs/hour ⁽³⁾	4,500 lbs/hour ⁽³⁾	5,000 lbs/hour ⁽³⁾	6,500 lbs/hour ⁽³⁾	9,000 lbs/hour ⁽³⁾
Horsepower:	78	102	102	116	153	198
Gearboxes:	Direct Drive Planetary Individual per shaft	Direct Drive Planetary Individual per shaft	Direct Drive Planetary Individual per shaft	Direct Drive Planetary Individual per shaft	Direct Drive Planetary Individual per shaft	Direct Drive Planetary Individual per shaft
Cart Lift:	Alpine ShurGrip	Alpine ShurGrip	Alpine ShurGrip	Alpine ShurGrip	Alpine ShurGrip	Alpine ShurGrip
Unload System:	Keith Walking Floor	Keith Walking Floor	Keith Walking Floor	Alpine Xpress Conveyor	Alpine Xpress Conveyor	Alpine Xpress Conveyor
Cart Storage:	2 - 96 Gallon	2 - 96 Gallon	2 - 96 Gallon	4 - 96 Gallon	4 - 96 Gallon	4 - 96 Gallon
Remote Curbside:	Engine / PTO / Start / Stop	Engine / PTO / Start / Stop	Engine / PTO / Start / Stop	Engine / PTO / Start / Stop	Engine / PTO / Start / Stop	Engine / PTO / Start / Stop
Vision System:	1 Camera / Monitor	1 Camera / Monitor	1 Camera / Monitor	3 Cameras / 2 Monitors	3 Cameras / 2 Monitors	3 Cameras / 2 Monitors
Controls:	Relay Logic	Relay Logic	Relay Logic	Relay Logic	Relay Logic	IQAN PLC
Safety Systems:	Access Door Interlocks 2 E-Stops	Access Door Interlocks 2 E-Stops	Access Door Interlocks 2 E-Stops	Access Door Interlocks 2 E-Stops	Access Door Interlocks 2 E-Stops	Access Door Interlocks 2 E-Stops
OTHER OPTIONS	V19	V26	V33	EVOLUTION	STAK	V-MAX
Payload Camera:	Optional	Optional	Optional	Standard	Standard	Standard
Backup Camera:	Optional	Optional	Optional	Standard	Standard	Standard
Shred Load Detection:	Optional	Optional	Optional	Optional	Optional	Optional
Hard Drive Punch:	Optional	Optional	Optional	Optional	Optional	Optional
Toolbox:	Optional	Optional	Optional	Optional	Optional	Optional
Cold Weather Package:	Optional	Optional	Optional	Optional	Optional	Optional
Weight Scale NTEP:	Optional	Optional	Optional	Optional	Optional	Optional
Custom Paint:	Optional	Optional	Optional	Optional	Optional	Optional
Custom Graphics:	Optional	Optional	Optional	Optional	Optional	Optional



⁽¹⁾ GVWR based on axle ratings
⁽²⁾ Payload based on empty factory weights
⁽³⁾ Throughput varies with material
© 2012 Alpine Shredders Limited. All Rights Reserved.
The Information provided here is subject to change without notice.



CALL TOLL FREE: 866-246-5634

www.AlpineShredders.com
Info@AlpineShredders.com